



UL 3133

Product Description

 Rated voltage
600V

 Rated temperature
150°C

 Fire Performances
Horizontal flame

 AWG
30AWG-4/0AWG

 ²⁹CU Conductor
Solid / Stranded

 Insulation
SR

 Bend Radius
10X

Marking Example:
E209277 cUL AWM STYLE 3133 150°C 600V FT2 □□AWG
3A AWM IA 150°C 600V □□AWG FT2 3A LF



SR Insulation(SR導體) Conductor(導體)



| Conductor | | | Insulation | |
|-----------|-------------------------------|--------------------------|--|---------------------------------|
| AWG 線規 | Stranded (No./mm) 線規/線徑 | Diameter (mm) 絞合外徑 | Insulation Thickness (mm) 絕緣厚度(mm) | OVERALL DIAMETER 完成外徑(mm) |
| 4/0 | 2146/0.254 | 15.70 | 0.82 | 15.23±0.1 |
| 3/0 | 1615/0.254 | 13.65 | 0.82 | 13.43±0.1 |
| 2/0 | 1330/0.254 | 12.36 | 0.82 | 12.34±0.1 |
| 1/0 | 1026/0.254 | 10.85 | 0.82 | 11.04±0.1 |
| 2 | 665/0.254 | 8.74 | 0.82 | 9.21±0.1 |
| 4 | 420/0.254 | 6.94 | 0.82 | 7.66±0.1 |
| 6 | 259/0.254 | 5.46 | 0.82 | 7.20±0.1 |
| 8 | 161/0.254 | 3.72 | 0.82 | 5.35±0.1 |
| 10 | 105/0.254 | 3.01 | 0.82 | 4.65±0.1 |
| 12 | 65/0.254 | 2.37 | 0.82 | 4.01±0.1 |
| 14 | 41/0.254 | 1.88 | 0.82 | 3.52±0.1 |
| 16 | 26/0.254 | 1.50 | 0.82 | 3.14±0.1 |
| 18 | 34/0.18 | 1.21 | 0.82 | 2.86±0.1 |
| 20 | 21/0.18 | 0.95 | 0.82 | 2.60±0.1 |
| 22 | 17/0.16 | 0.76 | 0.82 | 2.41±0.1 |
| 24 | 11/0.16 | 0.62 | 0.82 | 2.26±0.1 |
| 26 | 7/0.16 | 0.49 | 0.82 | 2.13±0.1 |
| 28 | 7/0.127 | 0.39 | 0.82 | 2.03±0.1 |
| 30 | 7/0.10 | 0.31 | 0.82 | 1.95±0.1 |

AWM UL 758

3A Plus, 3a plus (logo), and 3A (logo) are trademarks.
Other logos, product and/or Company names may be trademarks of their respective owners

<https://www.3awire.com/>

All Rights Reserved.

The information provided by 3A PLUS is intended for general informational purposes only and should not be construed as professional advice. While we strive for accuracy and completeness, we make no guarantees regarding the reliability, suitability, or availability of the information presented. Any reliance you place on such information is strictly at your own risk. We reserve the right to modify our products, services, and policies at any time without prior notice. For specific inquiries or concerns, please contact us directly. Thank you for choosing 3A PLUS Wire & Cable.