



UL 3347
Product Description

Rated voltage
300V

Rated temperature
80°C

Fire Performances
Horizontal flame

AWG
32AWG-16AWG

Conductor
Solid / Stranded

Insulation
XLPE

Bend Radius
10X

Marking Example:
E209277 cUL AWM STYLE 3347 80°C 300V FT2 □□AWG
3A AWM 1A 80°C 300V □□AWG FT2 3A LF



Conductor			Insulation	
AWG 線規	Stranded (No./mm) 線規/線徑	Diameter (mm) 絞合外徑	Insulation Thickness (mm) 絕緣厚度(mm)	OVERALL DIAMETER 完成外徑(mm)
16	26/0.254	1.50	0.47	2.43±0.1
18	34/0.18	1.21	0.47	2.15±0.1
20	21/0.18	0.95	0.47	1.89±0.1
22	17/0.16	0.76	0.47	1.69±0.1
24	11/0.16	0.62	0.47	1.55±0.1
26	7/0.16	0.49	0.47	1.42±0.1
28	7/0.127	0.39	0.47	1.32±0.1
30	7/0.10	0.31	0.47	1.24±0.1
32	7/0.08	0.24	0.47	1.18±0.1

AWM UL 758

3A Plus, 3a plus(logo), and 3A (logo) are trademarks.
Other logos, product and/or Company names may be trademarks of their respective owners