



300V FEP Wire

UL1332

Product Description

Rated voltage

300V

Rated temperature

200°C

Fire Performances

Horizontal flame

AWG

30AWG-10AWG

Conducto

Solid / Stranded(Silver plated)

Insulation

FEP

Covering

Optional (FEP)

Bend Radius

5X

Marking Example:
E209277 cUL AWM STYLE 1332 200°C 300V FT2 □□AWG
3A AWM IA 200°C 300V □□AWG FT2 3A LF

FEP Insulation (鐵氟龍絕緣) Conductor(導體)

Conductor		Insulation		OVERALL DIAMETER
AWG 線規	Stranded (No./mm) 線規/線徑	Insulation Thickness (mm) 絕緣厚度(mm)	Covering (mm) 外被厚度(mm)	
10	105/0.254	0.57	0.31	4.77±0.1
12	65/0.254	0.57	0.31	4.13±0.1
14	41/0.254	0.57	0.31	3.64±0.1
16	26/0.254	0.57	0.31	3.26±0.1
18	34/0.18	0.57	0.31	2.20±0.1
20	21/0.18	0.57	0.31	2.05±0.1
22	17/0.16	0.57	0.31	2.53±0.1
24	11/0.16	0.57	0.31	2.38±0.1
26	7/0.16	0.57	0.31	2.25±0.1
28	7/0.127	0.57	0.31	2.15±0.1
30	7/0.10	0.57	0.31	2.07±0.1

AWM UL 758

3A Plus, 3a plus(logo), and 3A (logo) are trademarks.
Other logos, product and/or Company names may be trademarks of their respective owners